Dig Safe #____

Town of Hampton Department of Public Works 100 Winnacunnet Rd. Hampton, NH 03842

603-926-4402 \$200 Fee Fax: 603-929-1913

| TREN | NCH APPLICATION | <u>ON</u> | |
|---|----------------------|--------------------------|------------------|
| For Consent To Lay/Repair Facilities In A Public High | way | | |
| Name of Company: | | | |
| Consent under RSA 255 as now or hereafter amended in: Name of Road: | | • | · |
| For the Purpose of: | | | |
| Excavated Trench Dimensions: Width | | | |
| Crossings to be made: | Open Trench or Punch | | |
| Pavement size to be disturbed: | | | |
| ☐ Check if completely off pavement | | | |
| Location must be premarked. | | | |
| Work to begin:o'clock | ck AM PM | Date: | |
| To be completed:o'clock | ck AM PM | Date: | |
| Must provide three (3) work days notice before wo | rk can begin. | | |
| Traffic officer to be required: | | | |
| I HAVE READ AND HEREBY AGREE TO COMPLY SIDE OF APPLICATION | WITH THE CONI | DITIONS SHOWN ON THIS | SIDE AND REVERSE |
| Dated: | | Ву: | |
| | | For: | |
| | | Contact: | |
| | | Phone #: | |
| Consent Granted: | | | |
| Dated: | | Ву: | |
| Comments: Milling of patch 12" beyond patch joint "infrared patch treatment" in Condition | | | leted in lieu of |
| ☐ If checked, a full width overlay is required. Joi | | w PW standard detail. | |
| Hampton Police Department 603-929-5800 Hampton Public Works Department 603-929-1913 | | oton Fire Department | 603-929-1915 |
| Actual Date of Excavation: | | Actual Beginning Time: _ | |
| Contact Name: | | | |
| Contact Number: | | Signature | |
| Date Inspected by Public Works: | | Signature | |

CONDITIONS

- 1. This consent may be revoked at any time.
- 2. Encumbrances or obstructions shall at all times be properly guarded, barricaded or fenced and lights shall be maintained throughout the night giving warning thereof.
- 3. The applicant shall indemnify and save harmless the Town issuing permit, for all claims for damage or injury whatsoever that may arise from the encumbrance, obstruction, occupation or use of said highway.
- 4. Shade trees shall not be cut down, trimmed or otherwise injured except as the excavation requires, and with specific permission in each case.
- 5. The highway shall be left in as good a condition of repair and cleanliness at the expiration of this consent as existed when this consent was granted with all backfill made and compacted as required by the Town.
- 6. The applicant shall restore the highway or cause the same to be restored for the following five (5) years by reason of such work.
- 7. Advertisements, notices, and signs shall not be displayed on or attached to any barricade or fence in any highway.
- 8. The applicant shall indemnify and save harmless the Town for all claims for damage or injury whatsoever that may be done to any public or privately owned utility in connection with the work contemplated under this application.
- 9. This consent shall be kept with the foreman of the applicant having the work in charge at the place where the work is being performed and shall be produced for examination upon request of any authorized representative of the Town.
- 10. Backfill from bottom trench to within 21" of finish grade must be a material acceptable to the Director of Public Works or his designated agent compacted to 95%. Lifts of fill not to exceed 12" loose. Fill to be compacted with a mechanical compactor.
- 11. The next 12" will be a gravel equal to material described in Division 300, Section 304.2 of N.H. Standard Spec. for Road and Bridge construction compacted to 95%. Fill to be compacted with a mechanical compactor.
- 12. The next 6" will be a gravel equal to material described in Division 300, Section 304.3. Fill to be compacted with a mechanical compactor.
- 13. Pavement will be saw cut 12" beyond excavated area. Cuts to be square.
- 14. 2" binder course will be installed as described in Division 400, Section 403. Joints shall receive a coating of emulsion before patching.
- 15. 1" wearing course will be installed as described in Division 400, Section 403. Joints shall receive a coating of emulsion before patching.
- 16. After one (1) year has passed since the installation of the 1" wearing course, the trench shall receive "infrared patch treatment" by a contractor approved by the Dept. of Public Works. In lieu of infrared treatment, the Highway foreman may allow crack sealing of the joints with an approved product. The applicant shall be responsible for the cost of this work.
- 17. To the extent possible, the Dept. of Public Works shall not allow excavation in new or reconstructed areas for a period of up to five (5) years.
- 18. A five (5) year escrow account shall be established with the Town in the amount of: \$5000, 1-5 trench permits; \$15,000, 5 or more, prior to the issuance of a trench permit.